CP PLUS

CP- LNC-FL20-80

Floodlight Camera

Main Features

- 1/2.7" 2MP Progressive Scan CMOS
- Max 25fps@1080P
- H.264 and MJPEG stream encoding
- Built-in Speaker and Built-in Microphone
- 3.6mm lens
- Indoor: IR Range of 10 meters, Outdoor: 20 meters, Memory Card
- Mobile Software: Android, iOS

CE FC RoHS COMPLIANT

**Product casing and specifications are subject to change without prior notice*

CP PLUS

CP- LNC-FL20-80

Floodlight Camera

Feature	Specification
Image Sensor	1/2.7" 2MP Progressive Scan CMOS
Minimum Illumination	0.3Lux
Wattage	12W
CCT	3000K
Lumens	800
Lifetime (hours)	20,000
White Balance	Auto/Manual
Gain Control (AGC)	Auto/Manual
Lens	3.6mm
Back Light Compensation	Auto/Manual
Video Compression	H.264/MJPEG
DNR	3D-DNR
Angle of View	90°
Video Streaming	25fps(Max)
Resolution	1920x1080, 1280x720
ICR	ICR infrared filter functional within 15 meters distance
Audio Compression	G.711/G.726
Audio	Built-in Speaker & Built-in Microphone
Bit Rate	64kbps-4Mbps
PIR Detection	120°
MicroSD Card	Max.128GB
Wi-Fi	WiFi802.11 b/g/n Wi-Fi connection @ 2.4GHz only
Wireless Frequency	2.4 GHz ~ 2.4835 GHz
Protocol	TCP/IP, HTTP, TCP, ICMP, UDP, ARP, IGMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP, ONVIF etc
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
Smart Phone	iPhone, iPad, Android Phone
IR	Outdoor: 20 meters, indoor: 10 meters (sensitive to environmental change)
Siren	Remote-activated 110-decibel alarm
Operating Temperature	-28°C to 65°C/Weather-resistant

CE FC RoHS COMPLIANT

**Product casing and specifications are subject to change without prior notice*

CP PLUS

CP- LNC-FL20-80

Floodlight Camera

Feature	Specification
Power Source	110-260V
Power Consumption	1.5-3W (Camera running all functions)
Mounting Base	4¾-inch (12.065-cm) diameter
Dimension	137 x 130 x 130 mm
Weight	1.1 KG

*Product casing and specifications are subject to change without prior notice