

CP- UNK-410D-W

HD Network Control Keyboard



Main Features

- Four Dimensional Joystick Control of PTZ Functions
- RS232, RS485 and Network Connections (Wi-Fi)
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control
- Support 4K decoding live view
- Support 4CH HDMI output
- Support snapshot and recording to U-disk
- Support Video-Wall display control and bidirectional talk
- Auxiliary Functions, OSD and operation guides Control





CP- UNK-410D-W

HD Network Control Keyboard

Feature

Main Processor

Operation System

Screen Video Output

Stream Type

Decoding Capability

Display split

Audio

Keyboard Connector

Alarm In Alarm Out

Loudspeaker

Network Mode

USB Interface

Wi-Fi

Power Supply

Power Consumption

Working Temperature
Working Humidity

Atmosphere Pressure

Dimension

Weight

Specification

Dual-core Braswell Processor

Embedded LINUX 4.2.0

10.1" TFT LCD touch screen (1280x800)

4×HDMI(extension decoding display)

H.265, H.264, H264H, H264B, MJPEG, MPEG4, SVAC, SmartH.264 and non standard

4CH@12MP(20fps)/4CH@4K(30fps)/6CH@5MP(30fps)/8CH@4MP(30fps)/10CH@3MP

(30fps)/16CH@2MP(30fps)

1/4/9/16

1 RS485, 2 RS232, 1 RS422

1 pair 3.5mm jack, support bidirectional talk

4, High-low level

4 (3 relay, 1 12V_1A)

2xRJ-45 port (10/100/1000M)), Wi-Fi

2 USB3.0, 2 USB2.0

Support (2.4GHz)

DC12V, 4A

25W(max), 18W(standby)

-10~+55°C

10%~95%

86kpa~106kpa

425mmx194mmx59mm (W×D×H) (exclude joystick)

3.73kg

