

CP- UVR-0801F1-HC**8 Ch. 1080P Cosmic HD DVR****Main Features**

- Auto Adaptive HDCVI/AHD/TVI/CVBS/IP signals
- Support upto 6MP IP Camera
- H.265+/H.265 dual-stream video compression
- Max 48Mbps Incoming Bandwidth
- All channel 1080P Non-Realtime Recording
- Support 1 SATA HDD up to 6TB, 2 USB Ports(2.0)
- HDMI / VGA Simultaneous Video Output
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UVR-0801F1-HC

8 Ch. 1080P Cosmic HD DVR



Feature

Processor
Operating System
IP Camera Input
Two-way Talk
User Interface
Video Input
Video Output
Compression
Video Resolution
Resolution
Video Recording
Video Display Split
Audio Input
Audio Output
Motion Detection
Video Loss
Audio Compression
Camera Blank
Smart Phone
Audio Sample Rate
Hard Disk
Audio Bit Rate
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode

Specification

Embedded processor
Embedded LINUX
8+4 Ch., each channel up to 6MP
Reuse audio in/out, RCA
GUI
8 channel, BNC
1 HDMI, 1 VGA
H.265+/H.265/H.264+/H.264
1920×1080, 1280×1024, 1280×720
5M-N, 4M-N, 1080P, 1080N, 720P, 960H, D1, CIF
Main Stream: 1st & 2nd channels 5M-N(1~10fps); other channels 4M-N/1080P(1~15fps); 1080N/720P/960H/ D1/CIF (1~25/30fps), Sub stream: CIF/QCIF (1~15fps)
1/4/8/9
1 channel, RCA
1 channel, RCA
MD Zones: 396 (22 × 18)
Supports
AAC (only for the 1st channel), G.711A, G.711U, PCM
Supports
iPhone, iPad, Android Phone
8KHz, 16 bit Per Channel
1 SATA port, up to 6TB
64Kbps Per Channel
Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Manual, Schedule (General, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Time /Date, Alarm, MD and Exact Search (accurate to second)
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom
USB Device/Network



**CP- UVR-0801F1-HC**
8 Ch. 1080P Cosmic HD DVR**Feature**

Interface Ports

Max User Account

Record Interval

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

1 HDMI, 1 VGA, 2 USB2.0

128 users

1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

RJ-45 port (100M)

HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 16.12, CGI Conformant

DC12V/1.5A

<10W(without HDD)

-10°C ~ +45°C (+14°F ~ +113°F), 10 ~ 90% RH

197mm x 192mm x 41mm

0.54kg (without HDD)