

CP- UNC-LA41ZPL5-MD**4MP WDR Network IR Bullet Camera - 50Mtr.****Main Features**

- 1/3" 4MP PS CMOS Image Sensor (0.84667 cm)
- Max. 4MP(2560 × 1440)@25/30fps and 4MP(2688 × 1520)@20fps
- H.265+ and H.264+ dual-stream encoding
- WDR(120dB), Day/Night (ICR), 3D-DNR,ROI, AWB, AGC, BLC, HLC
- 2.8mm~12mm Motorized Lens
- IR Range of 50 Mtrs, IP67, Micro SD Card, PoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro

CP- UNC-LA41ZPL5-MD

4MP WDR Network IR Bullet Camera - 50Mtr.

Feature

Image Sensor
 Minimum Illumination
 Effective Pixels
 Shutter Speed
 White Balance
 Lens
 Gain Control (AGC)
 Video Compression
 Angle of View
 Back Light Compensation
 Video Streaming
 Resolution
 Motion detection
 Privacy Mask
 ROI
 Bit Rate
 Protocol
 Ethernet
 Event Trigger
 User Account
 Smart Phone
 IR
 Micro SD
 Operating Temperature

Specification

1/3" 4MP Progressive scan CMOS (0.84667 cm)
 0.03Lux@F1.7
 2688(H) x 1520(V)
 Auto/Manual, 1/3~1/100000s
 Auto/natural/street lamp/outdoor/manual/regional custom
 2.8mm~12mm Motorized lens
 Auto/Manual
 H.265+/H.265/H.264+/H.264/H.264B; MJPEG
 Horizontal: 98°-31° Vertical: 55°-18° Diagonal: 116°-36°
 BLC / HLC / WDR(120dB)
 Main Stream: 2688 x 1520 (1 fps-20 fps) 2560 x 1440 (1 fps-25/30 fps)
 Sub Stream: 704 x 576 (1 fps-20/25 fps) 704 x 480 (1 fps-20/30 fps)
 2688 x 1520 (2688 x 1520); 2560 x 1440 (2560 x 1440); 2304 x 1296 (2304 x 1296); 1080p (1920 x 1080); 1.3M (1280 x 960); 720p (1280 x 720); D1 (704 x 576/704 x 480); VGA (640 x 480)
 OFF/ON (4 areas, rectangular)
 4 areas
 Yes (4 areas)
 H.264: 32 Kbps-6144 Kbps, H.265: 12 Kbps-6144 Kbps
 HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; RTMP; Multicast; HTTPS; SFTP; 802.1x; ICMP; IGMP; ONVIF (Profile S/Profile G); InstaOn; CGI
 RJ-45 (10/100Base-T)
 Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection
 20 Users
 iPhone, iPad, Android Phone
 IR Range of 50 Mtr.
 FTP; Micro SD card (support max. 256 GB); NAS
 -30°C to +55°C (-22°F to +131°F) /less than≤95%

CP- UNC-LA41ZPL5-MD**4MP WDR Network IR Bullet Camera - 50Mtr.****Feature**

Power Source
Power Consumption
Weatherproof Standard
Casing
Dimension
Weight

Specification

DC12V, PoE (802.3af)
< 7.5W (PoE)
IP67
Metal + Plastic
243.5 mm × Φ90.7 mm
0.44 kg