

CP- UNC-TD41L8-MD**4MP WDR IR Bullet Camera - 80Mtr.****Main Features**

- 1/3" 4Megapixel PS CMOS Image Sensor (0.84667 cm)
- 25/30fps@4M(2688x1520)
- Instastream, H.265 and H.264 triple-stream encoding
- WDR(120dB), Day/Night (ICR), 3DNR, AWB, AGC, BLC
- 3.6mm fixed lens (6mm, 8mm, 12mm optional)
- IR Range of 80 Mtrs, IP67, IK10, Micro SD Card, PoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UNC-TD41L8-MD

4MP WDR IR Bullet Camera - 80Mtr.

Feature

Image Sensor

Effective Pixels

Minimum Illumination

Shutter Speed

White Balance

Lens

Gain Control (AGC)

Video Compression

Angle of View

Back Light Compensation

Video Streaming

Resolution

Digital Zoom

Motion detection

Privacy Mask

ICR

ROI

Bit Rate

Protocol

Smart Detection

Ethernet

User/Host

IR

Smart Phone

Micro SD

Operating Temperature

Power Source

Power Consumption

Weatherproof Standard

Specification

1/3" 4Megapixel progressive scan CMOS (0.84667 cm)

2688(H) x 1520(V)

0.03Lux/F1.9(Color,1/3s,30IRE) 0.2Lux/F1.9(Color,1/30s,30IRE) 0Lux/F1.9(IR on)

Auto/Manual, 1/3~1/100000s

Auto/Natural/Street Lamp/Outdoor/Manual

3.6mm (6mm, 8mm, 12mm optional)

Auto/Manual

Instastream/H.265/H.264+/H.264

H: 81° (51°, 38°, 25°), V: 44° (29°, 21°, 14°)

BLC / HLC / WDR(120dB)

Main Stream: 4M(1~25/30fps), Sub Stream: D1(1~25/30fps), Third Stream: 1080P(1~14/4fps)

4M(2688×1520)/3M(2304×1296)/ 1080P(1920×1080)/1.3M(1280×960)/ 720P(1280×720)/D1 (704×576/704×480)/ VGA(640×480)/CIF(352×288/352×240)

16x

Off / On (4 Zone, Rectangle)

Off / On (4 Area, Rectangle)

Auto (ICR) / Color / B/W

Off / On (4 Zone)

H.264: 192K ~ 10240Kbps H.265: 80K ~ 8192Kbps

HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP; ONVIF, PSIA, CGI

Tripwire, Intrusion, Object Abandoned/Missing, Face Detection

RJ-45 (10/100Base-T)

20 Users

IR Range of 80 Mtr.

iPhone, iPad, Android Phone

Micro SD card 512GB

-40° C ~ +60° C (-40° F ~ +140° F) / Less than 95% RH

DC12V, PoE (802.3af)

<12W

IP67 & IK10

CP- UNC-TD41L8-MD**4MP Full HD WDR IR Bullet Camera - 80Mtr.****Feature**

Casing

Dimension

Weight

Specification

Metal

244.1mm×79mm×75.9mm

0.84kg