

CP- UNC-TE61ZL10E-VMD**6MP WDR IR Network Bullet Camera - 100Mtr.****Main Features**

- 1/2.9" 6MP PS CMOS Image Sensor
- 20fps@6MP(3072×2048),25/30fps@4MP(2688×1520)
- H.265+ /H.264+ triple-stream encoding
- WDR, Day/Night (ICR), 3D-DNR, ROI, AWB, AGC, BLC, HLC
- 7mm ~35mm Motorized Lens
- 2/1 Alarm in/out, 1/1 audio in/out
- IR Range of 100 Mtrs, Micro SD Card, IP67, IK10, ePoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UNC-TE61ZL10E-VMD

6MP WDR IR Network Bullet Camera - 100Mtr.

Feature

Image Sensor
 Effective Pixels
 Minimum Illumination
 Shutter Speed
 White Balance
 Lens
 Lens Type
 Max. Aperture
 DORI Distance
 Gain Control (AGC)
 Angle of View
 Video Compression
 S/N Ratio
 Back Light Compensation
 Video Streaming
 Resolution
 Digital Zoom
 Motion detection
 Privacy Mask
 ICR
 ROI
 Audio Input
 Audio Output
 Audio Compression
 Alarm IN
 Alarm Out
 Protocol

Specification

1/2.9" 6MP Progressive scan CMOS
 3072(H)x2048(V)
 0.03Lux/F1.4 (Color,1/3s,30IRE) 0.3Lux/F1.4 (Color,1/30s,30IRE) 0Lux/F1.4(IR on)
 Auto/Manual, 1/3~1/100000s
 Auto/Natural/Street Lamp/Outdoor/Manual
 7mm~35mm Motorized
 Motorized/ Auto Iris (HALL)
 F1.4
 W- 234m (Detect), 94m (Observe), 47m (Recognize), 23m (Identify)
 T- 765m (Detect), 306m (Observe), 153m (Recognize), 76m (Identify)
 Auto/Manual
 H:32°~10° , V:22°~8°
 H.265+/H.265/H.264+/H.264
 More than 50dB
 BLC/ HLC/ WDR
 Main Stream: 6MP(1~20fps)/4MP(1~25/30fps), Sub Stream: D1(1~25/30fps),
 Third Stream: 720P(1~25/30fps)
 6MP(3072×2048)/5MP(3072×1728)/ 5MP(2592×1944)/ 4MP(2688×1520)/ 3MP(2048×1536)/
 3MP(2304×1296)/ 1080P(1920×1080)/1.3M(1280×960)/ 720P(1280×720)/
 D1(704×576/704×480)/ VGA(640×480)/ CIF(352×288/352×240)
 16x
 Off / On (4 Zone, Rectangle)
 Off / On (4 Area, Rectangle)
 Auto (ICR)/Color/B/W
 Off / On (4 Zone)
 1 Channel
 1 Channel
 G.711a/ G.711Mu/ AAC/ G.726
 2 channel In: 5mA 5VDC
 1 channel Out: 300mA 12VDC
 HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS;
 UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP; ONVIF; PSIA; CGI



CP- UNC-TE61ZL10E-VMD

6MP WDR IR Network Bullet Camera - 100Mtr.

Feature

Bit Rate
Streaming Method
Smart Detection
Ethernet
User Account
IR
Smart Phone
Micro SD
Operating Temperature
Power Source
Power Consumption
Weatherproof Standard
Casing
Dimension
Weight

Specification

H.264: 24~10240Kbps , H.265: 14~9984Kbps
Unicast / Multicast
Tripwire, Intrusion, Object Abandoned/Missing, Face Detection
RJ-45 (10/100Base-T)
20 Users
IR Range of 100 Mtr.
iPhone, iPad, Android Phone
Micro SD, Max 128GB
-30°C~+60°C, Less than 95% RH
DC12V, ePoE, PoE (802.3af)
<12.95W
IP67 & IK10
Metal
273.2mm x 95.0mm x 95.0mm
1.11Kg