

**CP- UNR-32****32 Ch. H.264 4K Super Network Video Recorder****Main Features**

- Up to 32 channel IP camera input
- Up to 12Mp resolution preview and playback
- Max 384Mbps incoming bandwidth
- Support 8 SATA HDDs up to 48TB, 4 USB(2 USB3.0), 1 eSATA port
- Support iSCSI to expand storage space
- 2 HDMI / 1 VGA simultaneous video output
- Support Multi-brand network cameras
- Support RAID 0/1/5/6/10/50/60
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



# CP-UNR-32

## 32 Ch. H.264 4K Super Network Video Recorder

### Feature

Processor  
Operating System  
IP Camera Input  
Two-way Talk  
User Interface  
Video Output  
Compression  
Video Resolution  
Video Recording  
Video Display Split  
Motion Detection  
Video Loss  
Camera Blank  
Alarm Input  
Alarm Output  
Hard Disk  
Smart Phone  
VCA  
Trigger Events  
HDD Management  
Recording Mode  
Search Mode  
Playback  
Backup Mode  
Max User Account  
Interface Ports  
Record Interval  
Ethernet  
Protocols

### Specification

Dual-core embedded processor  
Embedded LINUX  
32 channel  
1 channel Input, 1 channel Output, RCA  
GUI  
2 HDMI(up to 3840× 2160), 1 VGA  
H.264H / H.264 / MJPEG  
3840× 2160, 1920× 1080, 1280× 1024, 1280× 720, 1024× 768  
Max 256 Mbps  
The 1st screen: 1/4/8/9/16/25/36, The 2nd screen: 1/4/8/9/16  
MD Zones: 396(22×18).  
Supports  
Supports  
16ch, low level effective, green terminal interface  
8ch, Relay contact(1A@24VDC), NO/NC programmable, green terminal interface  
8 SATA III ports, up to 48TB, 1 eSATA port  
iPhone, iPad, Android, Windows Phone  
Crossing line, Intrusion Detection, Object counting, Tampering, Object Removal  
Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips  
Single, Raid 0/1/5/6/10/50/60 (Support global HDD hot-spare)  
Manual, Schedule(Regular(Continuous), MD(Video detection: Motion detection, Camera blank, Video loss), Alarm), Stop  
Time/Date, Alarm, MD & Exact search (accurate to second), Smart search  
128Mbps in Raid 5 mode, 64Mbps in single HDD mode  
USB Device/Network/Internal SATA burner/eSATA Device  
128 users  
2 HDMI, 1 VGA, 4 USB ports(3 USB2.0, 1 USB3.0), 1 RS485, 1 RS232, 2 RJ45  
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
2 RJ-45 port (10/100M/1000M), 2 Ethernet ports joint working or 2 independent 1000Mbps Ethernet ports  
HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.4

**CP- UNR-32****32 Ch. H.264 4K Super Network Video Recorder****Feature**

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

**Specification**

AC110V~240V, 50~60Hz

40W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

482mm × 450mm × 91mm

&lt;9kg (without HDD)