

CP- UNR-4K2041-4PG

4 Ch. 4G Network Video Recorder





Main Features

- Support up to 4Ch. IP Camera Input
- H.265/H.264 dual codec decoding
- Up to 8MP resolution preview and playback
- Max 80Mbps incoming bandwidth
- Support 1 SATA HDDs up to 8TB, 2 USB ports(2.0), 4PoE Ports
- Support 4G Network (Embedded 4G Sim Card slot)
- Support Wi-Fi. ONVIF Version 2.4 conformance
- Support Multi-brand network cameras
- HDMI / VGA simultaneous video output
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



















CP- UNR-4K2041-4PG

4 Ch. 4G Network Video Recorder



Feature Specification

Dual-core embedded processor Processor

IP Camera Input 4 channel

Embedded LINUX Operating System

1 channel Input, 1 channel Output, RCA Two-way Talk

User Interface GUI

Video Output 1 HDMI, 1 VGA Compression H.265/H.264

Video Resolution 3840×2160, 1920×1080, 1280×1024, 1280×720, 1024×768 Video Recording Max 80 Mbps, 8MP/6MP/5MP/4MP/3MP/1080P/ 720P/ D1&etc.

Video Display Split 1/4

Motion Detection MD Zones: 396(22×18).

Video Loss Supports Camera Blank Supports

Smart Phone iPhone, iPad, Android Phone Hard Disk 1 SATA III ports, up to 8TB

Trigger Events Recording, PTZ, Tour, Video Push, Snapshot, and Screen Tips

Recording Mode Manual, Schedule (Regular (Continuous), MD, Stop Search Mode Time/Date, MD & Exact search (accurate to second)

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous Playback

camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

Backup Mode USB Device / Network

Interface Ports 1 HDMI, 1 VGA, 2 USB Ports(1 Rear USB2.0, 1 Front USB2.0)

Max User Account 128 users

Record Interval 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

Wi-Fi 802.11a/n/g, IEEE802.11b

3G TD-LTE. FDD-LTE. WCDMA, (Backward compatibility with 2G), 4G Supported

Ethernet 1 RJ-45 port (10/100Mbps), 4PoE Ports (IEEE802.3at/af)

HTTP, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, DNS, IP Filter, DDNS, IP Search, ONVIF Ver-Protocols

sion 2.4, CGI Conformant

Power Supply Single, DC48V/1.25A

NVR: <5.3W (without HDD), PoE: Max 25.5w for single port, 50w in total **Power Consumption**





CP- UNR-4K2041-4PG

4 Ch. 4G Network Video Recorder



Feature

Working Temp Dimensions

Weight

Specification

-10 ~+55°C / 10~90%RH / 86~106kpa 260mm×224.9mm×47.6mm 0.8kg (without HDD)

