

**CP- UNR-4K4324-V2****32 Ch. H.265+ 4K Network Video Recorder****Main Features**

- Up to 32 channel IP camera input
- H.265+/H.264+ dual codec decoding
- Up to 8MP resolution preview and playback
- Max 200Mbps incoming/ 96Mbps outgoing bandwidth
- Support 4 SATA HDDs up to 24TB, 2 USB(1 USB3.0)
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



**CP- UNR-4K4324-V2****32 Ch. H.265+ 4K Network Video Recorder****Feature**

Processor  
IP Camera Input  
Operating System  
Two-way Talk  
User Interface  
Video Output  
Compression  
Video Resolution  
Video Recording  
Video Display Split  
Motion Detection  
Video Loss  
Camera Blank  
Alarm Input  
Alarm Output  
Hard Disk  
Smart Phone  
Trigger Events  
Recording Mode  
Search Mode  
Playback  
Backup Mode  
Interface Ports  
Max User Account  
Record Interval  
Ethernet  
Protocols

**Specification**

Dual-core embedded processor  
32 channel  
Embedded LINUX  
1 channel Input, 1 channel Output, RCA  
GUI  
1 HDMI, 1 VGA  
Smart H.265+/H.265/Smart H.264+/H.264  
3840×2160, 1920×1080, 1280×1024, 1280×720, 1024×768  
Max 200Mbps  
1/4/8/9/16/25/36  
MD Zones: 396(22×18).  
Supports  
Supports  
16 Channel, Low Level Effective, Green Terminal Interface  
4 Channel, NO/NC Programmable, Green Terminal Interface  
4 SATA III ports, up to 24TB  
iPhone, iPad, Android Phone  
Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips  
Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Tampering, Video Loss), Stop  
Time/Date, Alarm, MD & Exact search (accurate to second), Smart search  
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom  
USB Device/Network  
1 HDMI, 1 VGA, 2 USB (1USB 3.0), 1 RS485, 1 RS232  
128 users  
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
2 RJ-45 port  
HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, ICMP, IGMP, SNMP, FTP, IP Search, ONVIF 2.4, SDK, CGI Conformant



 **CP- UNR-4K4324-V2****32 Ch. H.265+ 4K Network Video Recorder****Feature**

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

**Specification**

AC 100~240V, 50/60 Hz

&lt;13.7W (Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm x 411.1mm x 76mm

4.7kg (without HDD)