

**CP- UNR-4K5328-V2****32 Ch. H.265+ 4K Network Video Recorder****Main Features**

- Up to 32 channel IP camera input
- Max 320Mbps incoming bandwidth
- Smart H.265+ /H.265/Smart H.264+ /H.264/MJPEG
- Up to 12MP resolution preview and playback
- Support 8 SATA HDDs up to 10TB each, 4 USB Ports (2 USB3.0, 2USB2.0)
- 2 HDMI / 2 VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



# CP- UNR-4K5328-V2

## 32 Ch. H.265+ 4K Network Video Recorder

### Feature

Processor  
IP Camera Input  
Operating System  
Two-way Talk  
User Interface  
Video Output  
Compression  
Video Resolution  
Video Recording  
Video Display Split  
OSD  
Bit Rate  
Motion Detection  
Video Loss  
Camera Blank  
Alarm Input  
Alarm Output  
Smart Phone  
Hard Disk  
Trigger Events  
Recording Mode  
Decoding Capability  
Search Mode  
Playback  
Backup Mode  
Max User Account  
Record Interval  
Interface Ports

### Specification

Quad-core embedded processor  
32 channel  
Embedded LINUX  
1 Channel Input, 2 Channel Output, RCA  
GUI  
2 HDMI, 2 VGA  
Smart H.265+/H.265/Smart H.264+/H.264/MJPEG  
HDMI1: 3840 × 2160 , 1920 × 1080 , 1280 × 1024 , 1280 × 720 , 1024 × 768;  
VGA1: 1920 × 1080 , 1280 × 1024 , 1280 × 720 , 1024 × 768; HDMI2/VGA2: 1920 × 1080  
Max 320Mbps  
1/4/8/9/16/25/36  
Camera title, Time, Camera lock, Motion detection, Recording  
16Kbps ~ 20Mbps Per Channel  
MD Zones: 396(22×18).  
Supports  
Supports  
16 channel  
6 channel  
iPhone, iPad, Android Phone  
8 SATA ports, up to 10TB Each, 1 eSATA port  
Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips  
Manual, Schedule (Regular, MD (Motion Detection) , Alarm, IVS), Stop  
4-ch@8MP(30fps), 16-ch@1080P(30fps)  
Time/Date, Alarm, MD & Exact search (accurate to second)  
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom  
USB Device/Network/eSATA Device  
128 users  
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
4 USB Ports (2 Rear USB 3.0 , 2 Front USB 2.0 ) , 1 RS485, 1 RS232

# CP- UNR-4K5328-V2

## 32 Ch. H.265+ 4K Network Video Recorder

### Feature

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

### Specification

2 RJ-45 Ports (10/100/1000Mbps) Independent or Joint Working

HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search, ONVIF 2.4, SDK, CGI

Single, AC 100~240V, 50/60 Hz

<16.7W (without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm x 450.1mm x 95mm

6.55 kg (without HDD)