

CP- VNC-V4KZR3-VMD**4K WDR Array Vandal Dome Camera - 30Mtr.****INDIGO****Main Features**

- 1/2.5" 8MP PS CMOS Image Sensor
- Max 30fps@4K
- Ultra 265, H.265, H.264, MJPEG Triple-stream encoding
- WDR (120dB), Day/Night (ICR), 2/3D-DNR, Corridor Mode, ROI, AWB, AGC, BLC, HLC
- 2.8~12mm Motorized Lens
- IR Range of 30 Mtrs, Micro SD Card, IP67, IK10, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS

**Instastream****CE FC** **RoHS**
COMPLIANT

CP- VNC-V4KZR3-VMD

4K WDR Array Vandal Dome Camera - 30Mtr.



Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Lens
 Gain Control (AGC)
 Angle of View
 Video Compression
 Back Light Compensation
 S/N Ratio
 Video Streaming
 Resolution
 Video Output
 Frame Rate
 Privacy Mask
 ICR
 Motion Detection
 ROI
 Audio Input
 Audio Output
 Audio Compression
 Alarm IN
 Alarm Out
 Protocol
 Smart Detection
 Ethernet
 OSD
 IR

Specification

1/2.5" 8MP Progressive scan CMOS
 Colour: 0.02 Lux (F1.6, AGC ON) 0 Lux with IR
 Auto/Manual, 1/6~1/100000s
 Auto/Manual
 2.8~12mm Motorized Lens
 Auto/Manual
 79.6°~34.9°(H) , 64°~16.6°(V), 103.5°~42.9°(O)
 Ultra 265,H.265,H.264,MJPEG
 BLC/ HLC/ WDR(120dB)
 >55dB
 Triple
 3840×2160
 1 BNC, impedance 75 Ω; amplitude 1 V [p-p]
 Main Stream:8MP (3840×2160): Max. 30 fps, 2MP (1920×1080): Max. 30 fps; Sub Stream:2MP (1920×1080): Max. 30 fps; Third Stream:D1 (720×576): Max. 30 fps
 Up to 8 areas
 IR-cut filter with auto switch (ICR)
 Up to 4 areas
 Up to 8 areas
 impedance 35 kΩ; amplitude 2 V [p-p]
 impedance 600 Ω; amplitude 2 V [p-p]
 G.711
 1 IN
 1 Out
 IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, ONVIF (Profile S, Profile G, Profile T),API
 Intrusion, crossing line, Motion detection, Audio detection, Face detection, Defocus, Scene Change, Object Left, Object Moving, People counting
 1 RJ45 10M/100M Base-TX Ethernet
 Up to 8 OSDs
 Array Range of 30 Mtr.



 **CP- VNC-V4KZR3-VMD****4K WDR Array Vandal Dome Camera - 30Mtr.****Feature**

Micro SD
Audio
Operating Temperature
Humidity
Power Source
Power Consumption
Weatherproof Standard
Dimension
Weight

Specification

Micro SD, Up to 256 GB
Two-way audio Supported
-40°C ~ +60°C (-40°F ~ 140°F)
10%~95% RH (non-condensing)
DC12V±25%,PoE (IEEE802.3 af)
Max.8.7 W
IP67 & IK10
Φ148mm x 111.3 mm (Ø5.8" x 4.4")
0.92 kg