

CP- VNR-3104-4P**4 Ch. 4K 4PoE Network Video Recorder****Main Features**

- 4 Channel IP Camera Input
- Ultra H.265/H.265/H.264 Video Formats
- Support 4K Resolution Upto 8MP Recording
- 40Mbps Incoming/ 64Mbps Outgoing Bandwidth
- Support 1 SATA HDDs up to 10TB, 3 USB Ports, 4 PoE Ports
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



CP- VNR-3104-4P

4 Ch. 4K 4PoE Network Video Recorder

Feature

Processor

IP Camera Input

Operating System

Two-way Talk

User Interface

HDMI/VGA Output

Compression

Recording Resolution

Video Recording

Video Display Split

Corridor Mode Screen

Live view /Playback

Capability

Audio Input

Audio Output

Alarm Input

Alarm Output

Hard Disk

Playback

Interface Ports

Max User Account

Ethernet

Protocols

VCA Detection

VCA Search

Statistical Analysis

Specification

Dual-core embedded processor

4 channel

Embedded LINUX

1 channel, RCA

GUI

HDMI: 4K (3840x2160) /30Hz, 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz

VGA: 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz

Ultra H.265/ H.265 / H.264

8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

40Mbps

1/4

3/4

8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

1 x 4K@30, 2 x 4MP@30, 4 x 1080p@30

1 channel, RCA

1 channel, RCA

4 channel

1 channel

1 SATA ports, up to 10TB

4 Channel

3 USB Port

128

1 RJ-45 10M/100M Self-adaptive Ethernet Interface, 4 independent 100 Mbps PoE Network

P2P, UPnP, NTP, DHCP, PPPoE, ONVIF conformance: Profile S, Profile G, Profile T

Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking

Face search, Behaviour search

People counting

 **CP- VNR-3104-4P****4 Ch. 4K 4PoE Network Video Recorder****Feature**

Power Supply
Power Consumption
Working Temp
Working Humidity
Dimensions
Weight

Specification

48V DC , PoE: IEEE 802.3at, IEEE 802.3af
≤ 5 W , PoE: Max 30W for single port , Max 54W in total (13.5W for each)
-10°C ~ + 55°C (+14°F ~ +131°F)
10% ~ 90%
44mm × 260mm × 240mm (1.7" × 10.2" × 9.4")
≤ 1.12 Kg