

CP- VNR-3104LB-4P**4 Ch. 4PoE Network Video Recorder****INDIGO****Main Features**

- 4 Channel IP Camera Input
- Support Ultra 265/H.265/H.264 video formats
- Support HDMI and VGA simultaneous output
- 40Mbps Incoming/ 40Mbps Outgoing Bandwidth
- Support Up to 2MP Resolution Recording
- Support 1 SATA HDDs up to 8TB, 2 USB Ports, 4 PoE Ports
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



CP- VNR-3104LB-4P

4 Ch. 4PoE Network Video Recorder



Feature

Processor
Operating System
IP Camera Input
User Interface
Video Output
Compression
Video Resolution
Live Preview
Video Recording
Video Display Split
Corridor Mode Screen
Hard Disk
Capability
Playback
Max User Account
Interface Ports
Ethernet
Protocols
PoE
Power Supply
Power Consumption
Working Temp
Working Humidity
Dimensions
Weight

Specification

Dual-core embedded processor
Embedded LINUX
4 channel
GUI
HDMI, VGA
Ultra 265/H.265/H.264
HDMI: 1920x1080P@60Hz, 1920x1080P@50Hz, 1600x1200@60Hz, 1280x1024@60Hz, 1280x720@60Hz, 1024x768@60Hz, VGA: 1920x1080p@60Hz, 1920x1080p@50Hz, 1600x1200@60Hz, 1280x1024@60Hz, 1280x720@60Hz, 1024x768@60Hz
1080p/960p/720p/D1/2CIF/CIF
1080p/960p/720p/D1/2CIF/CIF
1/4
3/4
1 SATA ports, up to 8TB
4 x 1080p@20fps, 4 x 720p@30fps
4 Ch. , 1080p/960p/720p/D1/2CIF/CIF
128
2 USB Port (2.0)
1 RJ45 10M/100M self-adaptive Ethernet Interface
P2P, UPnP, NTP, DHCP, PPPoE, SSL,SNMP,TLS,HTTPS
4 independent 100 Mbps PoE network interfaces (IEEE 802.3at, IEEE 802.3af)
48V DC
≤5 W (without HDD) , PoE: Max 30W for single port , Max 54W in total (13.5W for each)
-10°C ~ + 55°C (+14°F ~ +131°F)
≤ 90% RH (non-condensing)
205mm × 205mm × 42mm(8.1" × 8.1" × 1.7")
0.64kg (without HDD)

