

CP- VNR-3108-8P**8 Ch. 4K 8PoE Network Video Recorder****Main Features**

- 8 Channel IP Camera Input
- Ultra H.265/H.265/H.264 Video Formats
- Support 4K Resolution Upto 8MP Recording
- 60Mbps Incoming/ 64Mbps Outgoing Bandwidth
- Support 1 SATA HDDs up to 10TB, 3 USB Ports, 8PoE Ports
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



CP- VNR-3108-8P

8 Ch. 4K 8PoE Network Video Recorder

Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface

HDMI/VGA Output

Compression
Recording Resolution
Video Recording
Video Display Split
Corridor Mode Screen
Live view /Playback
Capability
Audio Input
Audio Output
Alarm Input
Alarm Output
Hard Disk
Playback
Interface Ports
Max User Account

Ethernet
Protocols
VCA Detection
VCA Search
Statistical Analysis

Specification

Dual-core embedded processor
8 channel
Embedded LINUX
1 channel, RCA
GUI
HDMI: 4K (3840x2160) /30Hz, 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz
VGA: 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz
Ultra H.265/ H.265 / H.264
8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
60Mbps
1/4/8
3/4/5/7/9
8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
1 x 4K@30, 2 x 4MP@30, 4 x 1080p@30, 8 x 720p@30
1 channel, RCA
1 channel, RCA
4 channel
1 channel
1 SATA ports, up to 10TB
8 Channel
3 USB Port
128
1 RJ-45 10M/100M Self-adaptive Ethernet Interface, PoE: 8 independent 100 Mbps PoE Network interfaces
P2P, UPnP, NTP, DHCP, PPPoE, ONVIF conformance: Profile S, Profile G, Profile T
Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking
Face search, Behaviour search
People counting

 **CP- VNR-3108-8P****8 Ch. 4K 8PoE Network Video Recorder****Feature**

Power Supply
Power Consumption
Working Temp
Working Humidity
Dimensions
Weight

Specification

52V DC , PoE: IEEE 802.3at, IEEE 802.3af
≤ 5 W , PoE: Max 30W for single port , Max 108W in total (13.5W for each)
-10°C ~ + 55°C (+14°F ~ +131°F)
10% ~ 90%
44mm × 260mm × 240mm (1.7" × 10.2" × 9.4")
≤ 1.12 Kg