

CP- VNR-3108**8 Ch. 4K Network Video Recorder****Main Features**

- 8 Channel IP Camera Input
- Ultra 265/H.265/H.264 dual Video Formats
- Support 4K Resolution Upto 8MP Recording
- 48Mbps Incoming/ 48Mbps Outgoing Bandwidth
- Support 1 SATA HDDs up to 10TB, 2 USB Ports
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



CP- VNR-3108

8 Ch. 4K Network Video Recorder

Feature

Processor
IP Camera Input
Operating System
User Interface
HDMI/VGA Output
Compression
Recording Resolution
Video Recording
Video Display Split
Corridor mode screen
Live view/Playback
Capability
Audio Output
Hard Disk
Playback
Interface Ports
Max User Account
Ethernet
Protocols
Power Supply
Power Consumption
Working Temp
Working Humidity
Dimensions
Weight

Specification

Dual-core embedded processor
8 channel
Embedded LINUX
GUI
HDMI: 4K (3840x2160)/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Ultra 265, H.265, H.264
8MP, 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
40Mbps
1/4
3/4/5/7/9
8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
1 x 4K@30, 2 x 4MP@30, 4 x 1080p@30, 8 x 720p@30
1 channel, RCA
1 SATA ports, up to 10TB
8 Channel
2 USB Port
128
1 RJ-45 10M/100M Self-adaptive Ethernet Interface
P2P, UPnP, NTP, DHCP, PPPoE, ONVIF conformance: Profile S, Profile G, Profile T
12V DC
≤ 5 W
-10°C ~ + 55°C (+14°F ~ +131°F)
10% ~ 90%
43.6mm × 240.2mm × 260.0mm (1.7" × 9.5" × 10.2")
≤ 1 Kg