

CP- VNR-3108B**8 Ch. Network Video Recorder****INDIGO****Main Features**

- 8 Channel IP Camera Input
- Support Ultra 265/H.265/H.264 video formats
- Support HDMI and VGA simultaneous output
- 40Mbps Incoming/ 40Mbps Outgoing Bandwidth
- Support Up to 2MP Resolution Recording
- Support 1 SATA HDDs up to 8TB, 2 USB Ports
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



CP- VNR-3108B

8 Ch. Network Video Recorder



Feature

Processor
Operating System
IP Camera Input
User Interface
Video Output
Compression
Video Resolution
Live Preview
Video Recording
Video Display Split
Corridor Mode Screen
Hard Disk
Capability
Playback
Interface Ports
Max User Account
Ethernet
Protocols
Power Supply
Power Consumption
Working Temp
Working Humidity
Dimensions
Weight

Specification

Dual-core embedded processor
Embedded LINUX
8 channel
GUI
HDMI, VGA
Ultra 265/H.265/H.264
HDMI: 1920x1080P@60Hz, 1920x1080P@50Hz, 1600x1200@60Hz, 1280x1024@60Hz, 1280x720@60Hz, 1024x768@60Hz, VGA: 1920x1080p@60Hz, 1920x1080p@50Hz, 1600x1200@60Hz, 1280x1024@60Hz, 1280x720@60Hz
1080p/960p/720p/D1/2CIF/CIF
1080p/960p/720p/D1/2CIF/CIF
1/4/8/9
3/4/5/7/9
1 SATA ports, up to 8TB
4 x 1080p@20fps, 4 x 720p@30fps
8 Ch. , 1080p/960p/720p/D1/2CIF/CIF
2 USB Port (Front panel: 1 x USB2.0 ; Rear panel: 1 x USB2.0)
128
1 RJ45 10M/100M self-adaptive Ethernet Interface
P2P, UPnP, NTP, DHCP, PPPoE
12V DC
≤3.2 W(without HDD)
-10°C ~ + 55°C (+14°F ~ +131°F)
≤ 90% RH (non-condensing)
260mm × 240mm × 44mm
0.9kg (without HDD)

