

# CP-XR-DN211-S

## 4G Router

- Compatible with WCDMA, FDD-LTE, TDD-LTE Default 802.11b/g/n
- LTE: B1/3/5/7/8/20/38/40/41 WCDMA: B1/5/8
- Support Wi-Fi 2.4G, Wi-Fi 2x2 MIMO, 802.11 b/g/n
- Support Internal antenna
- Support Reset, WPS



### About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.



# CP-XR-DN211-S

## 4G Router

Feature	Specification
<b>Hardware Specifications</b>	
4G Category	LTE CAT.4
4G/3G Standards	FDD LTE,TDD-LTE,WCDMA
4G Mobile Bands	4G FDD LTE:B1/B3/B5/B7/B8/B20/B28/; 4G TDD-LTE:B38/B40/B41; 3G WCDMA:B1/B5/B8
Max 4G Speed	DL:150Mbps; UL:50Mbps
Wi-Fi Standards	802.11b/g/n
Wi-Fi Frequency	2.4GHz
Wi-Fi Speed	2.4GHz:300Mbps
Interface	1 × 10/100Mbps LAN/WAN Port 1 × 2FF SIM Card Slot (Mini SIM Card)
Button	WPS/Reset
Antennas	Internal 4G/3G Antennas; Internal Wi-Fi Antennas
LED Indicators	Power; Wi-Fi; LAN/WAN; Internet; 4G/3G Signal strength (4 Bars)
Dimensions (LxWxH)	166.0mm x 120.2mm x 40.2mm
Weight	About 425g
Color	White
Power Supply	DC12V/1A
Power Consumption	<10W
<b>Software Specifications</b>	
Connection Mode	Automatic Mode, Cable Broadband Mode, Wireless Broadband Mode
WAN Type	4G/3G, Wired and Wireless

Feature	Specification
4G/3G Features	Auto-APN; Auto dial-up; SMS (Send/Receive/Delete); Phonebook; Data limited; PIN Management
Wi-Fi Functions	Broadcast and Hide Wi-Fi name; Guest network
Wi-Fi Security	WEP, WPA-PSK, WPA2-PSK, WPA/WPA2
Software features	Local/remote management DHCP(DHCP Server and Client) Virtual Server (UPnP/DMZ/Port Forwarding/Port Filtering/Port Mapping) Firewall (Mac/IP address filter, Wi-Fi Black/Whilte list) Upgrade firmware from local or OTA IPV4 support
<b>Working Environment</b>	
Temperature	Operating Temperature: -10 °C to +65 °C Storage Temperature: -20 °C to +85 °C
Humidity	5% ~ 95%
Contents	1 x 4G LTE Router 1 x Ethernet cable 1 x Power adapter 1 x Quick Installation Guide